

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01 KTST01



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

General Description

A double sided tissue tape with a high tack Solvent Acrylic adhesive. Hand tearable, good conformity, with a stable liner and excellent ultraviolet and plasticiser resistance. Ideal for bonding metal, nameplates, cloth and plastic surfaces

Property	Value
Adhesive type	Solvent Acrylic
Adhesive thickness	0.09mm
Adhesion	0.4 kg/cm
Tensile Strength	0.71 kg/cm
Elongation at break	2%
Servicable temperature	-15 to + 120°C
Shelf Life	12 months stored in ambient room temp. conditions
Shelf Life (Solid Rubbers)	3-6 months

Change Control Date	Change
04/09/2014	Created



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

