

Specification Sheet / 01 KT148 Double Sided Tissue Tape



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

General description

This solvent acrylic adhesive combines high initial tack with good shear and peel results. The tissue base forms excellent cohesive strength. It has good resistance to UV, Plasticizer, Ageing and Moisture. Typical applications include laminating to foam and rubber for Automotive Industry.

Carrier

Description	Grade
Non-woven tissue	12 g/m ²

Release Liner

Grade	Colour	Weight
P E Paper	White	110 g/m ²

Adhesive

Type	Grade	Thickness
Solvent acrylic	High Performance	148 - 153 micron

Performance

Peel adhesion to steel	Loop tack	Release from liner	Temperature range
800 N/m	600 N/m	10 N/m	-10°C to 160°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		

Change Control Date	Change
20/07/2015	Created
12/01/2017	Adhesive thickness modified

The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

