

Specification Sheet (Superceded) / 01 EPDM Cord Material Composition



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

EPDM Sponge Cord density

0.6 g cm/3

Tolerance applicable

+/- 0.4mm

EPDM Cord Substance Details	Value
Bicyclo(2.2.1)hept-2-ene, 5-ethylidene-, polymer with ethene and 1-p... EPDM-rubber Ethylene/propylene/diene terpolymer	45.31
Zinc oxide	1.54
Stearic acid	0.31
Wax	0.9
Carbon black	27.22
Calcium-carbonate	10.57
Distillates (petroleum), solvent-refined light paraffinic	8.16
Toluene-4-sulfonohydrazide	0.06
C, C' -azodi (formamide)	1.2
Calcium-oxide	1.71
Polyethylene glycol	0.91
Sulphur	0.46
Di(benzothiazol-2-yl) disulphide	0.3
N-(Cyclohexylthio)phthalimide	0.15
Confidential substances	1.2
Change Control Date	Change
08/02/2017	Created



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

