

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



http://www.advancedseals.co.uk

## Specification Sheet / 01

### KT21AA \*FDA\* Double Sided Tissue Tape



ISO9001, ISO14001, ISO45001  
Certificate Ref: 11739

#### TOXICOLOGICAL INFORMATION

FDA approved for indirect food contact

#### Carrier

Description	Grade
P/E Scrim	Square

#### Release Liner

Grade	Colour	Weight
Glassine	White	80 g/m <sup>2</sup>

#### Adhesive

Type	Grade	Thickness
Rubber resin	Hi Tack	70 micron

#### Performance

Peel adhesion to steel	Loop tack	Release from liner	Temperature range
1200 N/m	1000 N/m	10 N/m	-10°C to 60°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		

#### Change Control Date

Change
Created



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

