

## Specification Sheet (Superceded) / 01 Expanded PVC Foam 130kg



ISO9001, ISO14001, ISO45001  
Certificate Ref: 11738

| Parameters                | Units              | Values    | Norm |
|---------------------------|--------------------|-----------|------|
| Adhesive                  |                    | Acrylic   |      |
| Density                   | kgs/m <sup>3</sup> | 130       |      |
| Tensile Strength          | N/cm <sup>2</sup>  | 30        |      |
| Elongation                | %                  | >155      |      |
| Shore 00 Hardness         |                    | 35        |      |
| Force to compress         | Ncm <sup>2</sup>   | 3.2       |      |
| Service Temperature Range | °C                 | -30 / +70 |      |
| Application Temperature   | °C                 | 10-40     |      |
| Fungi Resistance          |                    | Excellent |      |
| UV Resistance             |                    | Excellent |      |
| Shelf Life                |                    | 2 Years   |      |

| Change Control Date | Change  |
|---------------------|---------|
| 25/4/2017           | Created |



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

