

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



http://www.advancedseals.co.uk

Specification Sheet (Superceded) / 01 KT62E Acrylic Scrim Filmic Liner



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

Carrier			
Description		Grade	
P/E Scrim		Square	
Release Liner			
Grade	Colour	Weight	
Polyester	Clear	36 Micron	
Adhesive			
Type	Grade	Thickness	
Acrylic	Hi-Tack	80 micron	
Perfomance			
Peel adhesion to steel	Loop tack	Release from liner	Temperature range
1000 N/m	700 N/m	10 N/m	-20°C to 120°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubber)	3-6 months		
Change Control Date		Change	
03/09/2013		Created	



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

