

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01

3050A Hot Melt Scrim Adhesive Tape



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

Carrier

Description	Grade	Scrim Colour
PET Scrim	Square	White

Release Liner

Grade	Colour	Thickness
Glassine	Amber	0.080mm

Adhesive

Type	Grade	Thickness
Rubber resin	High Tack	0.050mm

Performance

Adhesion	Static Shear	Release from liner	Temperature range
480 N/m	24 hours	15 N/m	-0°C to 60°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		

Change Control Date	Change
10/12/13	Created
03/09/2019	Black Diamond PET Scrim Discontinued. Details removed from specification



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

