

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: [technical@advancedseals.co.uk](mailto:technical@advancedseals.co.uk)



<http://www.advancedseals.co.uk>

## Specification Sheet / 01 A350 CMRB



ISO9001, ISO14001, ISO45001  
Certificate Ref: 11739

### Product description

Polyether polyurethane foam which meets the requirements of schedule 1 part 1 of the furniture and furnishing (fire safety) regulations

### Typical Properties

Density Range	48 - 52 kg/m <sup>3</sup>	BS EN ISO 845:1995
Hardness Strenght (40%)	225 - 265 N	BS EN ISO 2439
Nominal Tensile Strength	Min 50 kPa	BS EN ISO 1798
Nominal Elongation at Break	Min 90%	BS EN ISO 1798
Nominal Compression Set	Max 8%	BS EN ISO 1856
Standard Colour	White	

### For product sample and to find out more, contact us

Change Control Date	Change
27/05/2022	Created



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

