

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk

ASG

advanced
seals + gaskets

<http://www.advancedseals.co.uk>

Specification Sheet / 01 A352 FR 60ppi



ISO9001, ISO14001, ISO45001
Certificate Ref: 11738

| Test | Method | Unit | Specification |
|-----------------------------|------------|-------------------|---------------|
| Density | ISO845 | kg/m ³ | 26-32 |
| Compression load deflection | ISO 3386/1 | kPa | 2.6-4.6 |
| Tensile strength | ISO 1798 | kPa | 115 min |
| Elongation at break | ISO 1798 | % | 190 min |
| Cell-count | . | 1/cm | 14-17 |
| PPI Number | . | PPI | 50-70 |
| Flammability | ISO 3795 | mm/min | Max 100 |

| Change Control Date | Change |
|---------------------|---------|
| 25/07/2019 | Created |



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.



ASG