

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01 KT83AA Double Sided Filmic Tape



ISO9001, ISO14001, ISO45001
Certificate Ref: 11739

Technical Data

Carrier Description		Carrier Grade	
Polyprop		12 Micron	
Release Liner Grade	Release Liner Colour	Release Liner Weight	
Glassine	Amber	80 GSM	
Adhesive Type	Adhesive Grade	Adhesive Thickness	
Hot Melt	GP	70 Micron	
Peel adhesion to steel	Loop tack	Release from liner	Temperature Range
1200 N/m	1000 N/m	10 N/m	-20°C to 120°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		
Change Control Date		Change	
22/08/2022		Created	



The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

