

## Specification Sheet / 01 KT22A Rubber Resin Scrim Tape



ISO9001, ISO14001, ISO45001  
Certificate Ref: 11738

<b>Carrier</b>			
<b>Description</b>		<b>Grade</b>	
Polyester		12 micron	
<b>Release Liner</b>			
<b>Grade</b>	<b>Colour</b>	<b>Weight</b>	
Glassine	White	80 g/m <sup>2</sup>	
<b>Adhesive</b>			
<b>Type</b>	<b>Grade</b>	<b>Thickness</b>	
Rubber resin	Hi Tack	70 micron	
<b>Performance</b>			
<b>Peel adhesion to steel</b>	<b>Loop tack</b>	<b>Release from liner</b>	<b>Temperature range</b>
1200 N/m	1000 N/m	10 N/m	-10°C to 60°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		
10/12/13	Created		
<b>Change Control Date</b>		<b>Change</b>	



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

