

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

## Specification Sheet / 01 KT82E Acrylic Scrim



Certificate No. 11738-EMS-001  
ISO 9001:2015 ISO 14001:2015

<b>Carrier</b>			
<b>Description</b>		<b>Grade</b>	
P/E Scrim			
<b>Release Liner</b>			
<b>Grade</b>	<b>Colour</b>	<b>Weight</b>	
Glassine	Amber	80 g/m²	
<b>Adhesive</b>			
<b>Type</b>	<b>Grade</b>	<b>Thickness</b>	
Acrylic	Hi-Tack	80 micron	
<b>Perfomance</b>			
<b>Peel adhesion to steel</b>	<b>Loop tack</b>	<b>Release from liner</b>	<b>Temperature range</b>
1000 N/m	700 N/m	10 N/m	-20°C to 120°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubber)	3-6 months		
<b>Change Control Date</b>		<b>Change</b>	
03/09/2013		Created	



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

