

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: [technical@advancedseals.co.uk](mailto:technical@advancedseals.co.uk)



<http://www.advancedseals.co.uk>

## Specification Sheet / 01 KT60A Hot Melt Transfer Tape



Certificate No. 11738-EMS-001  
ISO 9001:2015 ISO 14001:2015

Property	Value
Release liner grade	PET
Release liner colour	Clear
Release liner weight	36 micron
Adhesive type	Rubber resin
Adhesive thickness	40 micron
Adhesive grade	GP

Peel adhesion to steel	Loop tack	Release from liner	Temperature range
1000 n/m	1000 n/m	10 n/m	-10 °c to 60 °c
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		

Change Control Date	Change
23/11/2015	Created



The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

