

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

## Specification Sheet (Superceded) / 01 KT51EE Double Sided Tissue Tape



Certificate No. 11738-EMS-001  
ISO 9001:2015 ISO 14001:2015

Carrier			
Description		Grade	
Shelf Life		12 months stored in ambient temperature	
Non-woven tissue		12 g/m²	
Release Liner			
Grade	Colour	Weight	
Glassine	Amber	80 g/m²	
Adhesive			
Type	Grade	Thickness	
Waterbased acrylic	Modified	80 micron	
Perfomance			
Peel adhesion to steel	Loop tack	Release from liner	Temperature range
800 N/m	600 N/m	10 N/m	-20°C to 120°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		
Change Control Date		Change	
03/09/2013		Created	



The above figures are average values.  
We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

