

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet (Superceded) / 01 A352 60PPI FR Reticulated Foam



Certificate No. 11738-EMS-001
ISO 9001:2015 ISO 14001:2015

Test	Value
Pore Size (visual guide)	60 ppi
Density ISO 845 Kg/m ³	26-32
Tensile Strength ISO 1798 kpa minimum	50
Elongation @ break ISO 1798 % minimum	100
Compression Load Deflection: kpa (ISO 3386)	2.0 - 4.0
Temperature Range Continuous (°C)	-30/+110
Standard Colour	Charcoal
Sheet Size	2m x 1m
Thickness	5mm+
Flammability: FMVSS 302	pass
Flammability: ISO 1795	pass

Change Control Date	Change
02/08/2013	Created



The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

