

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01

3050A Hot Melt Scrim Adhesive Tape



Certificate No. 11738-EMS-001
ISO 9001:2015 ISO 14001:2015

Carrier			
Description		Grade	Scrim Colour
PET Scrim		Square	White
Release Liner			
Grade		Colour	Thickness
Glassine		Amber	0.080mm
Adhesive			
Type		Grade	Thickness
Rubber resin		High Tack	0.050mm
Perfomance			
Adhesion	Static Shear	Release from liner	Temperature range
480 N/m	24 hours	15 N/m	-0°C to 60°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		
Change Control Date		Change	
10/12/13		Created	
03/09/2019		Black Diamond PET Scrim Discontinued. Details removed from specification	



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

