

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01 KT82A Rubber Resin Scrim Tape



Certificate No. 11738-EMS-001
ISO 9001:2015 ISO 14001:2015

Carrier			
Description		Grade	
Polyester		12 micron	
Release Liner			
Grade	Colour	Weight	
Glassine	Amber	80 g/m²	
Adhesive			
Type	Grade	Thickness	
Rubber resin	Hi Tack	70 micron	
Perfomance			
Peel adhesion to steel	Loop tack	Release from liner	Temperature range
1200 N/m	1000 N/m	10 N/m	-10°C to 60°C
Shelf Life	12 months stored in ambient room temp. conditions		
Shelf Life (Solid Rubbers)	3-6 months		
09/07/2020	Created		
Change Control Date		Change	



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

