

Polymer Works, Hope Street  
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



http://www.advancedseals.co.uk

## Specification Sheet / 01 KT83EE Double Sided Filmic Tape



Certificate No. 11738-EMS-001  
ISO 9001:2015 ISO 14001:2015

### Technical Data

| Carrier Description        |   | Carrier Grade        |                   |
|----------------------------|---|----------------------|-------------------|
| Polyprop                   |   | 12 Micron            |                   |
| Release Liner Grade        | Release Liner Colour                              | Release Liner Weight |                   |
| Glassine                   | Amber   | 80 GSM               |                   |
| Adhesive Type              | Adhesive Grade                                    | Adhesive Thickness   |                   |
| Acrylic                    | GP  | 70 Micron            |                   |
| Peel adhesion to steel     | Loop tack   | Release from liner   | Temperature Range |
| 1200 N/m                   | 1000 N/m  | 10 N/m               | -20°C to 120°C    |
| Shelf Life                 | 12 months stored in ambient room temp. conditions |                      |                   |
| Shelf Life (Solid Rubbers) | 3-6 months  |                      |                   |
| Change Control Date        |   | Change               |                   |
| 07/05/2014                 |   | Created              |                   |



The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.  
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.  
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

