

Polymer Works, Hope Street
Dudley, West Midlands DY2 8RS

t: 01384 252555

f: 01384 252373

e: technical@advancedseals.co.uk



<http://www.advancedseals.co.uk>

Specification Sheet / 01 KT8 Amber Release Paper



Certificate No. 11738-EMS-001
ISO 9001:2015 ISO 14001:2015

Properties

Weight Ø	$82 \pm 4 \text{ g/m}^2$	$50 \pm 2,5 \text{ \#/ream}$
Calliper Ø	$69 \pm 8 \text{ }\mu\text{m}$	$2,7 \pm 0,3 \text{ mil}$
Colour	Amber	
Tensile Strength MD [kN/m]	Ø 8,5	min. 6,0
Tear Strength CD [mN]	Ø 475	min. 400

Technical data are subject to change. Only data of the respective current product specification are valid. Testing of products fitness for their intended use is the exclusive responsibility of the user. Our datasheets and specifications do not release the user from conducting their own tests with regard to fitness of our products for the particular use intended by the user.

Change Control Date

14/10/2022

Change

Created



The above figures are average values.

We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No WI007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

