

Specification Sheet / 01

9111 Double-Sided Hot Melt Tissue Tape



ISO9001, ISO14001, ISO45001
Certificate Ref: 11738

Description

A double sided tissue tape with aggressive high bond strength. Suitable for a variety of applications e.g. foam laminating, fabrics & paper, general bonding, bag sealing, envelope sealing etc.

Property	Value
Thickness	100mu
Adhesive	Hot Melt
Tensile Strength	50 N/25mm
Elongation at break	4.0
Adhesion	21 N/25mm
Serviceable Temperature	-10 to + 60 °C
Shelf Life	12 Months

Adhesive Properties

Adhesion to steel	Open Side	840n/m	BS7116:1990-D
Adhesion to steel	Closed Side	840n/m	BS7116:1990-D
Shear adhesion	Open Side	40 hrs	BS7116:1990-B
Shear adhesion	Closed Side	40 hrs	BS7116:1990-B

Change Control Date

Change Control Date	Change
05/09/2013	Created



The above figures are average values.
We recommend that you examine any material you select to ensure its suitability for your application.
Tolerance(s) applied in accordance with ASG specification No W1007 (<https://bit.ly/3nKm6Hj>) unless otherwise stated.
Our standard terms and conditions of trading (<https://bit.ly/3b3mThw>) apply at all times.

